

2026年度製品一覧表(セミオーダートレ)

2026.8 株式会社トリオパッケージ

商品名	マス目(小さい順、mm)			外寸(mm)			標準材質	マス数	スタック
	縦	横	高さ	縦	横	高さ	カスタマイズ可		
TY200-1W	8.9	8.9	4	344	292.5	13.6	PS0.6帯電防止	200	○
TY50-1	12.2	9.6	6	150	100	6.5	PP0.5帯電防止	50	△
TY30-1	12.5	9.5	8	100	100	8.6	PS0.6帯電防止	30	△
TY100-1	17.3	15.3	11	276	188	11.4	PP0.4帯電防止	100	△
TY200-2	18.5	15.8	11	435	250	11.4	PP0.5帯電防止	200	△
TY100-2	20.5	14.5	10.5	256	203	10.9	PS0.4帯電防止	100	△
TY80-1	20.5	19.4	10.5	256	203	10.9	PP0.6帯電防止	80	△
TY100-3W	22	15.1	11	321	254	17.6	PP0.6帯電防止	100	○
TY80-2W	22.5	20.6	11	321	254	17.6	PP0.6帯電防止	80	○
TY150-1	23	18.4	11	435	250	11.4	PP0.5帯電防止	150	△
TY70-1W	24	22.5	11	321	254	17.6	PP0.6帯電防止	70	○
TY40-1	24.2	23.2	14	260	152	14.4	PS0.55	40	×
TY100-4	24.9	18.2	20	326	258	20	PS0.38	100	×
TY100-5	25.4	18.9	10	326	258	10.4	PS0.4帯電防止	100	△
TY60-1	27	20.1	20	321	254	26.6	PP0.6帯電防止	60	△
TY80-3	27.6	12.4	11	276	188	11.4	PP0.4帯電防止	80	△
TY60-2	28	20.5	10.5	256	203	10.9	PS0.4帯電防止	60	△
TY120-1	29	18.2	11	435	250	11.4	PP0.5帯電防止	120	△
TY70-2	29	29	20	353	255	20.4	PS0.4	70	×
TY60-3	29.6	22.2	10.5	256	202	16.3	PS0.3帯電防止	60	△
TY100-6W	30	12.5	10	320	260	10.6	PS0.4	100	○
TY150-2W	30	12.5	13	461	292.5	20.6	PS0.6帯電防止	150	○

TY60-4W	30	22.1	11	321	254	17.6	PP0.6帶電防止	60	○
TY50-2	30.2	21.2	11	276	188	11.4	PP0.4帶電防止	50	△
TS75W	30.4	30.4	21	461	292.5	21	PP0.6	75	○
TY80-4	30.4	27.5	22	461	292.5	22.4	PS0.4帶電防止	80	△
TY75-1W	30.4	30.4	18	461	292.5	21.4	PS0.4帶電防止	75	○
TY40-2	30.5	27.6	11	276	188	11.4	PP0.4帶電防止	40	△
TY80-5	30.6	21.8	15.7	360	220	16	PP0.3帶電防止	80	△
TY50-3W	31.5	21.5	16	321	254	22.6	PP0.6帶電防止	50	○
TY35-1	31.5	29	11	276	188	11.4	PP0.4帶電防止	35	△
TY70-3	32.8	12.5	11	276	188	11.4	PP0.4帶電防止	70	△
TY50-4W	33	20.1	20	321	254	26.6	PP0.6帶電防止	50	○
TY35-2W	33.4	31	20	321	254	26.6	PP0.6帶電防止	35	○
TY80-6	33.5	26	28.5	461	292.5	29	PS0.4	80	×
TY100-7	34	15.1	14	344	292.5	14.6	PS0.4帶電防止	100	△
TY40-3W	34	27.5	20	321	254	26.6	PP0.6帶電防止	40	○
TY50-5	34.3	20.3	10.5	256	203	10.9	PS0.4帶電防止	50	△
TS35W	35	35	40	353	254	40	PP0.6	35	○
TS40W	35	35	25	353	254	25	PP0.6	40	○
TY100-8W	35	9	8	344	292.5	14.6	PS0.6	100	○
TY100-9	35.5	20	28	461	292.5	28.4	PS0.4	100	×
TY80-7	36.2	27.5	25.5	461	292.5	26.3	PS0.8	80	×
TY100-10	37	18.6	11	435	250	11.5	PP0.5帶電防止	100	△
TY80-8	37.1	24.7	11	435	250	11.5	PP0.5帶電防止	80	△
TY100-11	37.8	22.4	11	461	292.5	11.5	PS0.5	100	△
TY60-5	39.2	12.5	11	276	188	11.4	PP0.4帶電防止	60	△
TY30-2W	39.3	33	20	321	254	26.6	PP0.6帶電防止	30	○

TY60-6	39.5	37.9	20	461	292.5	20.4	PS0.4	60	△
TY25-1W	40	19.1	12	260	152	18.5	PS0.5	25	○
TY32-1	40.5	28.2	11	276	188	11.4	PP0.4帯電防止	32	△
TY30-3W	40.6	35.1	11	321	254	17.6	PP0.6帯電防止	30	○
TY35-3	40.9	37.4	29	326	258	29.4	PS0.38帯電防止	35	△
TY50-6	41.3	37.8	28	461	292.5	28.4	PS0.4	50	△
TY50-7W	41.4	26	35	450	317	40.6	PS0.6帯電防止	50	○
TY40-4W	41.4	34.3	35	450	317	40.6	PS0.6帯電防止	40	○
TY50-8	42.6	37	11	435	250	11.5	PP0.5帯電防止	50	△
TY50-9	42.8	24.9	20	326	258	20	PS0.38	50	×
TY35-4W	43	35	11	420	225	17.5	PS0.5	35	○
TY50-10W	43.3	22.8	12	344	292.5	18.5	PS0.5	50	○
TY40-5	43.8	28.8	35	344	292.5	35.5	PS0.5帯電防止	40	△
TS20W	44	44	26	321	254	26	PP0.6	20	○
TY50-11	44	21	35	344	292.5	35.5	PS0.5帯電防止	50	△
TS24W	45	45	40	353	254	40	PP0.6	24	○
TY40-6W	45.2	28.3	12.5	344	292.5	19.1	PS0.6帯電防止	40	○
TY60-7	47	10	11	276	188	11.4	PP0.4帯電防止	60	△
TY30-4	47.3	23.8	11	276	188	11.4	PP0.4帯電防止	30	△
TY50-12	48	32.8	35	461	292.5	35.4	PS0.4	50	×
TY25-2W	48	33.5	20	321	254	26.6	PP0.6帯電防止	25	○
TY20-1W	48	44	20	321	254	26.6	PP0.6帯電防止	20	○
TY50-13	48.1	12.4	11	276	188	11.4	PP0.4帯電防止	50	△
TY40-7	48.1	48.1	28	461	292.5	28.4	PS0.4	40	×
TY75-2	48.2	22.3	25	461	292.5	25.4	PS0.4	75	×
TY25-3	48.2	30.5	11	276	188	11.4	PP0.4帯電防止	25	△

TY20-2	48.2	39.5	11	276	188	11.4	PP0.4帶電防止	20	△
TY50-14	49	33.8	28	461	292.5	28.4	PS0.4	50	×
TY25-4W	49.1	35.1	15	321	254	21.6	PP0.6帶電防止	25	○
TY45-1	49.2	39.2	25	461	292.5	25.4	PS0.4	45	×
TY40-8W	49.9	20.6	11	321	254	17.6	PP0.6帶電防止	40	○
TY20-3W	50	46	15	321	254	21.6	PP0.6帶電防止	20	○
TY10-1W	50.7	41.3	22	260	152	28.5	PS0.5帶電防止	10	○
TY30-5W	52	41.4	35	450	317	40.6	PS0.6帶電防止	30	○
TY25-5	54	44	35	344	292.5	35.5	PS0.5帶電防止	25	△
TY30-6	54.4	33.9	35	344	292.5	35.5	PS0.5帶電防止	30	△
TY40-9	54.7	37	11	435	250	11.5	PP0.5帶電防止	40	△
TY35-5	55.1	47.5	28	461	292.5	28.4	PS0.4	35	×
TY50-15W	55.5	10.5	10	360	205	16.5	PS0.5	50	○
TY50-16	56.5	18.9	11	321	254	11.4	PP0.4帶電防止	50	△
TY20-4W	56.6	55.2	11	321	254	11.4	PP0.4帶電防止	20	○
TY42-1	56.8	39.8	25	461	292.5	25.4	PS0.4	42	×
TY25-6	57.2	43.8	11	321	254	11.4	PP0.4帶電防止	25	△
TY36-1	60	32	35	461	292.5	35.8	PS0.8帶電防止	36	△
TY20-5W	60.6	50.5	35	450	317	40.6	PS0.6帶電防止	20	○
TY24-1W	61.8	47	9	450	256	15.5	PS0.5帶電防止	24	○
TY28-1	62.1	56.1	25	461	292.5	25.4	PS0.4	28	×
TY35-6W	64	39	24	493	340	30.6	PS0.6帶電防止	35	○
TY40-10W	64.7	22.2	35	450	317	40.6	PS0.6帶電防止	40	○
TY30-7W	64.7	30.3	35	450	317	40.6	PS0.6帶電防止	30	○
TY25-7W	64.7	41.4	35	450	317	40.6	PS0.6帶電防止	25	○
TY30-8	65	47.5	28	461	292.5	28.4	PS0.4	30	×

TY30-9	65.5	42.6	11	435	250	11.5	PP0.5帯電防止	30	△
TY50-17	66	23.2	28	461	292.5	28.5	PS0.5	50	△
TY36-2	67	39.2	25	461	292.5	25.4	PS0.4	36	×
TY24-2	67	62	25	461	292.5	25.4	PS0.4	24	×
TY25-8W	67.9	46.1	7	435	292.5	13.5	PS0.5	25	○
TY20-6W	68.9	20	15	290	180	21.5	PS0.52	20	○
TY30-10W	70	30	18	461	292.5	24.5	PS0.5	30	○
TY20-7	71	44	35	344	292.5	35.5	PS0.5帯電防止	20	△
TY20-8W	71.6	41.6	13	344	292.5	23.4	PS0.4帯電防止	20	○
TY20-9W	73	50	13	461	292.5	20.5	PS0.6	20	○
TY20-10W	74.1	52.2	9	435	250	14.3	PS0.3帯電防止	20	○
TY15-1W	76.8	64.7	35	450	317	40.6	PS0.6帯電防止	15	○
TY45-2	79.3	20.8	11	435	250	11.5	PP0.5帯電防止	45	△
TY15-2	79.3	74.4	11	435	250	11.5	PP0.5帯電防止	15	△
TY25-9	79.6	42.6	11	435	250	11.5	PP0.5帯電防止	25	△
TY25-10W	80	42.8	12	461	292.5	12.4	PS0.4帯電防止	25	○
TY25-11	80	47.5	28	461	292.5	28.4	PS0.4	25	×
TY30-11W	80.2	44.5	17	493	340	22.5	PS0.5帯電防止	30	○
TY20-11W	80.8	41.4	35	450	317	40.6	PS0.6帯電防止	20	○
TY20-12	81	51	28	461	292.5	28.4	PS0.4	20	×
TY15-3	85	81	20	461	292.5	20.4	PS0.4	15	×
TY20-13W	90.3	30.6	18.5	461	292.5	25.8	PS0.8	20	○
TY8-1	94.7	86.7	34	470	230	34.5	PS0.5帯電防止	8	×
TY10-2W	100	45	11	321	254	17.6	PP0.6帯電防止	10	○
TY20-14	101.9	46.8	28	461	292.5	28.4	PS0.4	20	×
TY32-2	103.5	25.9	25	461	292.5	25.4	PS0.4	32	×

TY16-1	103.9	62.1	25	461	292.5	25.4	PS0.4	16	×
TY12-1	104	85.2	25	461	292.5	25.4	PS0.4	12	×
TY10-3W	105.3	68.3	10	435	250	10.3	PS0.3帯電防止	10	○
TY20-15	115.4	25.3	24	461	292.5	24.5	PS0.45	20	×
TY15-4W	117	41.4	35	450	317	40.6	PS0.6帯電防止	15	○
TY10-4W	118.8	64	35	450	317	40.6	PS0.6帯電防止	10	○
TY15-5W	120	45.5	18	440	313	24.4	PS0.4帯電防止	15	○
TY9-1W	126.4	84	14	461	335	20.5	PS0.5帯電防止	9	○
TY20-16W	128.5	37.5	20	461	292.5	20.5	PS0.5帯電防止	20	○
TY10-5	130.7	81	25	461	292.5	25.4	PS0.4	10	×
TY14-1	131.7	56.1	25	461	292.5	25.4	PS0.4	14	×
TY12-2	131.7	66	25	461	292.5	25.4	PS0.4	12	×
TY18-1	132.7	41.2	23	461	292.5	23.4	PS0.4	18	×
TY20-17W	144	18.9	16	315	264	16.5	PVC0.5	20	○
TY18-2	153.7	46.5	21	493	340	21.5	PS0.5帯電防止	18	×
TY13-1W	164	41	26	493	340	32.5	PS0.5	13	○
TY10-6W	166.7	58.3	15	493	340	23.8	PS0.8	10	○
TY4-1W	173.7	121.2	35	450	317	40.6	PS0.6帯電防止	4	○
TY10-7W	181.8	41.4	35	450	317	40.6	PS0.6帯電防止	10	○
TY10-8W	203	34	19	485	243	25.5	PS0.5帯電防止	10	○
TY10-9W	208	33.7	10.5	485	243	17	PS0.5帯電防止	10	○
TY10-10W	225.8	41.6	10	487	252.5	10.5	PS0.5帯電防止	10	○
TY5-1W	248.5	64	35	450	317	40.6	PS0.6帯電防止	5	○
TY11-1	φ88.8	φ88.8	38	461	292.5	38.5	PS0.5帯電防止	11	×